



SCHEDULE

EC TYPE-EXAMINATION CERTIFICATE

Sira 10ATEX3279U
Issue 3

13 DESCRIPTION OF COMPONENT

The CV Breather Drain Plugs each comprise a hollow brass body that is threaded at one end to enable it to be fitted to the bottom of the associated 'Ex e' enclosure. The body contains a press-fitted sintered disc that allows moisture to pass out of the enclosure via two drain holes. These holes exit into the hexagonal socket which shrouds the drain holes and also provides a means of tightening the device.

The components are available with entry thread sizes between M16 and M32.

Design Options: An alternative body profile with three drain holes, in sizes M25 and M32 only.

Alternative materials of manufacture: Mild steel to BS 970:1983
Stainless steel to BS 970:1983
Glass filled nylon MDF2 900 (Not for Group I use)

Plating Options: Nickel, Zink, Electroless.
Nickel maximum thickness 0.008mm.

Alternative threadforms in equivalent sizes: Metric to ISO 965 PT 1 & 3
PG to DIN 40430:1971
BSPP to BS 2279:1985
ET to BS 31:1979
NPS to ANSI/ ASME B1.20.1 -1983
Any other threadform conforming to Table 3 f
EN/IEC 60079-1 and clauses C.2.2 & C.2.3.1 as applicable

Variation 1 - This variation introduced the following changes:

- i. The original product description was amended to correct typographical errors and omissions.
- ii. The list of supporting standards was clarified.
- iii. The addition of the Glass Filled Nylon MDF2 900 material option to the Type CV Breather/Drain, the description and marking being amended accordingly.
- iv. The marking for use in explosive dust atmospheres was corrected.
- v. The introduction of a Special Condition of Safe Use that clarifies the permitted temperature ranges.

Variation 2 - This variation introduced the following change:

- i. The recognition that the company name and address has changed from Raxton Ltd, Westgate, Aldridge, West Midlands WS9 8FS to EX Innovations Ltd., Trading as Raxton at Jepson Court, Tancred Close, Queensway, Royal Leamington Spa, Warwickshire CV31 3RZ.
- ii. The introduction of a Condition of Certification.



SCHEDULE

EC TYPE-EXAMINATION CERTIFICATE

Sira 10ATEX3279U
Issue 3

14 DESCRIPTIVE DOCUMENTS

14.1 Drawings

Refer to Certificate Annexe.

14.2 Associated Sira Reports and Certificate History

Issue	Date	Report number	Comment
0	03 November 2010	R22194A/00	The release of the prime certificate.
1	01 May 2012	R26410A/00	The introduction of Variation 1
2	09 November 2012	N/A	Issued to correct a typographical error in the marking
3	15 January 2013	R29745A/00	The introduction of Variation 2.

15 SPECIAL CONDITIONS FOR SAFE USE

- 15.1 The limiting temperature ranges of these devices depends upon the their material of manufacture and the type of 'O' ring used in their construction as defined by the manufacturer, the user shall therefore install these devices in accordance with temperature values stated in the table below:

'O'-ring Material	Limiting temperature	
	Brass, mild steel or stainless steel	Nylon MDF2 900
None	-50°C to +150°C	-20°C to +65°C
Nitrile	-20°C to +80°C	-20°C to +65°C
EPDM (fitted as standard)	-30°C to +125°C	-20°C to +65°C
Neoprene	-20°C to +100°C	-20°C to +65°C
Viton	-5°C to +150°C	-5°C to +65°C
Silicone	-30°C to +150°C	-20°C to +65°C
Fluorosilicone	-50°C to +150°C	-20°C to +65°C

16 ESSENTIAL HEALTH AND SAFETY REQUIREMENTS OF ANNEX II (EHSRs)

The relevant EHSRs that are not addressed by the standards listed in this certificate have been identified and individually assessed in the reports listed in Section 14.2.

17 CONDITIONS OF CERTIFICATION

- 17.1 The use of this certificate is subject to the Regulations Applicable to Holders of Sira Certificates.
- 17.2 Holders of EC type-examination certificates are required to comply with the production control requirements defined in Article 8 of directive 94/9/EC.
- 17.3 The CV Breather Drain Plugs that are constructed of Glass Filled Nylon MDF2 900 shall not be marked with any information that indicates that they are suitable for Group I use.
- 17.4 The manufacturer shall take all reasonable steps to ensure that the user can comply with the special conditions for safe use and shall advise the user in respect of the materials that are used in the construction of the devices.
- 17.5 Only Glass Filled Nylon type MDF2 900 shall be used in the manufacture of the non-metallic CV breather drains.
- 17.6 These products shall be marked in accordance with the information as specified in this certificate and related reports.

This certificate and its schedules may only be reproduced in its entirety and without change.

Sira Certification Service

Rake Lane, Eccleston, Chester, CH4 9JN, England

Tel: +44 (0) 1244 670900
Fax: +44 (0) 1244 681330
Email: info@siracertification.com
Web: www.siracertification.com

Certificate Annexe

Certificate Number: Sira 10ATEX3279U
Component: Breather Drain Type CV
Applicant: EX Innovations Limited Trading as Raxton



Issue 0

Drawing No.	Sheets	Rev.	Date (Sira stamp)	Title
832 A	1 of 1	-	11 Oct 10	CV Breather Drain Plugs

Issue 1

Drawing No.	Sheets	Rev.	Date (Sira stamp)	Title
811	1 of 1	1	30 March 12	Ex e Glass Filled Nylon Breather Plug
832	1 of 1	1	04 Apr 12	Ex e Glass Filled Nylon Breather Plug
832A	1 of 1	1	04 Apr 12	Ex e Glass Filled Nylon Breather Plug

Issue 2 No new drawings were introduced.

Issue 3

Drawing No.	Sheets	Rev.	Date (Sira stamp)	Title
MD - 01	1 of 1	1	14 Jan 13	Raxton Marking Label Drawing

This certificate and its schedules may only be reproduced in its entirety and without change.