

3 Lighting

11 Ceiling/wall mounted lighting

1 ATEX ceiling- or wall-mounted LED lighting e9312 serie

Are you looking for a small, explosion-protected light fitting for the illumination of hard-to-reach areas, areas with confined space conditions or with minimal requirements for illuminance? TheLED ceiling- or wall-mounted light fitting series e9312 is the perfect choice and is suited for zone 1, 2, 21 and 22.

Zone 0	✗	Zone 20	✗
Zone 1	✓	Zone 21	✓
Zone 2	✓	Zone 22	✓

IBExU20ATEX1092

It is robust, compact and the outer fixing points allow easy installation. Furthermore, the frosted impact-resistant PC cover ensures glare-free and homogenous illumination and, in combination with the sturdy wire guard, protects the light fitting against accidental damage.

Specifications

Housing	aluminium
Protection	IP66
Lamp	LED
LED colour	6500K
Cable entry	2 x M25 (1 gland, 1 plug)
Ambiant temperature	-25°C - +40°C
Guideline	ATEX
Manufacturer	Schuch



Ordering data

Code	Power	Construction	Luminous flux	Cable entry	Weight
e9312F/SK	11W	with wire guard	600lm	2 x M25	1,3kg
e9312F	11W	without wire guard	600lm	2 x M25	1,2kg

Dimensional sketches

