

The XAW-S fire alarms are an addition to the ASSEMBL-Y control units. The pushbutton can be manually or automatically operated after the glass has been broken. The fire alarms come complete with a hammer to break the glass.

Specifications

Protection	IP65
Mounting	with 2 or 4 mounting holes
Cable entry	1 gland (for a cable of 8 to 13 mm)
Material housing	glass-fibre reinforced polyester
Ambiant temperature	-25°C - +40°C

Ex II 2 G Ex d e IIC T6 Gb

Ex II 2 D Ex tb IIIC T85°C Db

Zone 0	✗	Zone 20	✗
Zone 1	✓	Zone 21	✓
Zone 2	✓	Zone 22	✓

INERIS03ATEX0122X



Ordering data

Code	Contact control	Contacts glass intact	Weight
XAW-S111	automatic after breaking of the glass	1NO	0,95 kg
XAW-S121	automatic after breaking of the glass	1NC	0,95 kg
XAW-S151	automatic after breaking of the glass	1NO+1NC	0,98 kg
XAW-S211	manually after breaking of the glass	1NO	0,95 kg
XAW-S221	manually after breaking of the glass	1NC	0,95 kg
XAW-S251	manually after breaking of the glass	1NO+1NC	0,98 kg

Dimensional sketches

